PO Box 518 620 Applegate St. Philomath, OR 97370



(541) 929-5650 Fax (541) 929-5277 www.wetlabs.com

# **Chlorophyll WETStar Characterization**

Date: February 20, 2015 S/N: WS3S-900P

Chlorophyll concentration expressed in µg/l can be derived using the equation:

 $CHL(\mu g/I) = Scale Factor \times (Output - Clean Water Offset)$ 

Analog output 0.056 V

Clean Water Offset (CWO) 0.056 VScale Factor (SF)  $14.9 \mu g/I/V$ 

Maximum Output 5.43 V Resolution 0.20 mV Ambient Characterization Temperature  $22 \pm 1^{\circ}$ C

Current Draw 30 mA @ 12V (typical)

12-hour Stability 0.16 mV/hr Temperature Stability, 25–2 °C 0.07 mV/°C

Range	
15 μg/l	0
74 μg/l	Χ
150 µg/l	0

#### Definitions:

CWO: Clean Water Offset value obtained using pure filtered de-ionized water.

**SF**: Scale Factor is used to convert the fluorescence response of the instrument into chlorophyll-a concentration. Scale Factor is determined at WET Labs during a cross calibration using a liquid fluorescent standard and a reference fluorometer whose chlorophyll fluorescence response has been characterized in a laboratory using a mono-species lab culture of *Thalassiosira weissfloqii* phytoplankton.

Maximum Output: Maximum signal output of the fluorometer.

Resolution: Standard deviation of 1 minute of clean water data, sampled once per second.

 $\textbf{Ambient Characterization Temperature:} \ \ \textbf{Room temperature at time of characterization}.$ 

Current Draw: The amount of current the instrument uses for operation.

12-hour Stability: Deviation of output averaged over 12 hours.

Temperature Stability: Measured output variation per degree.

WS3S-900P.xlsx Revision I 10/3/07

PO Box 518 620 Applegate St. Philomath, OR 97370



(541) 929-5650 Fax (541) 929-5277 www.wetlabs.com

## **WETStar Calibration and Repairs**

Date February 20, 2015 Customer Woods Hole Oceanographic Institute

S/N# WS3S-900P Repair Order 26167

#### **Standard Service**

• Performed noise test: 1 sample/sec for 60 sec

• Performed stability test: 1 sample/min for 12 hrs

• Performed temperature test: 25-2 °C

- Performed saturation test
- Shake-tested unit
- Pressure-tested unit
- Updated unit's calibration sheet

## **Diagnosis**

Evaluated Instrument and found the Red Filter was delaminating. Readings were drifting low.

## Repairs

Replaced the Red Filter and O-Rings. Retuned.

## **Comments**