



# Hyperion Fluorescein

Valeport's Hyperion Fluorometer sensor range delivers high performance measurements of Chlorophyll a, Phycocyanin, Fluorescein (Uranine), or Rhodamine in a compact & robust package ideal as a standalone sensor, for ROV and AUV integration or used with as part of a multi-sensor array and data logger.

Offered as standard in a 6000m depth rated, titanium housing the Hyperion Fluorometer has a wide range (9-28V DC) isolated power supply, data output up to 32Hz and RS232, RS485 and Modbus communications.

Hyperion Fluorometers can be supplied in a more rugged form that includes Acetal protection rings, a shaped anti-snag connector cover and a Kevlar weave protected cable.

## DATA SHEET

### Product Details



OPTICAL



DATALOG X2  
& ENVIROLOG  
SOFTWARE

**Valeport Limited**  
St. Peter's Quay, Totnes,  
Devon TQ9 5EW United Kingdom

Telephone: +44 (0) 1803 869292  
Email: [sales@valeport.co.uk](mailto:sales@valeport.co.uk)  
[www.valeport.co.uk](http://www.valeport.co.uk)



Fluorescein*	
<b>Excitation</b>	470 nm
<b>Detection</b>	545 nm
<b>Dynamic Range: gain setting is software controlled</b>	0-500 ppb 2 gain settings: 0-25, 0-500
<b>Minimum Detection (3x SD in RO water)</b>	0.01 ppb
<b>Linearity</b>	0.99 R2
<b>Response Time</b>	0.03 - 2 sec
<b>Output Rate</b>	0.5 Hz - 32 Hz (free running) software controlled

\* Calibrated against Fluorescein/Rhodamine solution

### Communications

The instrument will operate in real time, with set up performed by direct communications with a PC before and after deployment.

<b>RS232</b>	Up to 200m cable Direct to serial port via USB adapter
<b>Baud Rate</b>	2400 - 115200
<b>Protocol</b>	8 data bits, 1 stop bit, No parity, No flow control

### Electrical

<b>External</b>	9 – 28V DC Isolated
<b>Power</b>	<600mW
<b>Connector</b>	SubConn MCBH6F

### Software

Valeport supply DataLog x2 Windows software for instrument setup, data download and display.

### Physical

<b>Materials</b>	Titanium with Sapphire glass window
<b>Depth Rating</b>	6,000m
<b>Dimensions</b>	40mmØ x 179.5mm (including connector)
<b>Weight</b>	0.50 kg (in air) 0.26 kg (in water)
<b>Operating Temp</b>	-5°C - 35°C (the sensor is damaged above 60°C)

### Ordering

<b>0901001 - F</b>	Fluorescein (Uranine)
Supplied with: · 1x Hyperion Instrument · 1x 0.5m pig tail · Manual and transit case · DataLog x2 Software	

### Datasheet Reference: Hyperion Fluorometer | April 2020

As part of our policy of continuing development, Valeport Ltd. reserve the right to alter at any time, without notice, all prices, specifications, designs and conditions of sale of all equipment - Valeport Ltd © 2020

